

SIS WIRE VW-1

CSA

Conductor Stranded tinned copper
Insulation Colour Coded Flame Retardant XLPE
Temperature 90°C
Voltage 600V
Approvals UL Standard 44 – XHHW-2
 UL C 22.2 No.38
 CSA RW90



Application For use in switchboards and panel boards, power and control circuits in distribution systems, suitable for low toxicity applications and other electrical equipment and raceways not exceeding 600 volts.

Packaging X 300 m

Product Code	AWG Size	Strands	Insulation Thickness in. (mm)	Nominal O.D. in (mm)	Flame Rating	Cable Weight (lbs/mft)	Colours
34E1265	12	65/30	0.030 (0.76)	0.145 (3.68)	UL VW-1 CSA & FT2	25	GREY
34E1441	14	41/30	0.030 (0.76)	0.127 (3.23)	UL VW-1 CSA & FT2	19	GREY

GTF FIXTURE WIRE

Conductor Bare copper conductor
Insulation 16 - 14 AWG – 600V Thermoplastic and one lacquered glass braid insulation
 12 - 10 AWG – 600V Thermoplastic and two lacquered glass braids insulation
Temperature 125°C
Rating CSA standard C22.2 No. 127-1981
Packaging X 75, X 150 m



Product Code	AWG Size	Strands	Insulation Thickness in. (mm)	Nominal O.D. in. (mm)	Current (amp)	Cable Weight (lbs/mft)	Colours
34G1626	16	26	0.022 (0.56)	0.121 (3.07)	8	14	BLK/WHT
34G1441	14	41	0.022 (0.56)	0.137 (3.48)	17	19	BLK/WHT/GRN/ RED/BLUE
34G1265	12	65	0.030 (0.76)	0.187 (4.75)	23	31	BLK/WHT/RED
34G10105	10	105	0.030 (0.76)	0.209 (5.31)	28	53	BLK/WHT