

TYPE B MIL-W-16878 HOOK-UP WIRE

- Conductor** Soft annealed tinned copper
- Insulation** Colour coded PVC
- Temperature** -54C bend to +150C
- Applications** Internal wiring of electrical and electronic equipment, panels and meters.
- Packaging** 75m, 150m & 300m spools, long length reels



Product Code	Cond. Size	Cond. Strand	Nom. Insul. Thickness inches	Suggested Working Voltage	Nom. O.D. inches	Ship. Weight lbs/mft
34K2601	26	SOLID	.010	600	.037	1
34K2401	24	SOLID	.010	600	.041	2
34K2201	22	SOLID	.010	600	.046	3
34K2001	20	SOLID	.010	600	.054	4
34K1801	18	SOLID	.010	600	.062	7
34K1601	16	SOLID	.010	600	.073	9
34K2607	26	7	.010	600	.040	1
34K2407	24	7	.010	600	.045	2
34K2207	22	7	.010	600	.052	3
34K2010	20	7	.010	600	.059	4
34K1807	18	7	.010	600	.060	4
34K1816	18	16	.010	600	.068	7
34K1816	18	16	.010	600	.069	7
34K2219	22	19	.010	600	.054	3
34K2019	20	19	.010	600	.062	4
34K1619	16	19	.010	600	.079	9
34K1419	14	19	.010	600	.093	10