

# CCTV CABLE

## RG-59

<b>Conductor</b>	Bare copper
<b>Jacket</b>	Overall PVC
<b>Max. Voltage</b>	350V
<b>Nominal Impedance</b>	75 ohms
<b>Approvals</b>	EU CMG FT4
<b>Applications</b>	CCTV plus audio, pan and tilt CCTV control



Product Code	AWG	Strand & Cond.	Shield/ Coverage	Insulation Material	Insulation Nominal OD		Nominal OD		Nom. Cap. (pF/ft)	Cable Weight (lbs/mft)	Nominal Attenuation	
					in	mm	In	mm			mHz	Db/100ft
355591802	20 (CX)	Solid BC	95% BCB	FPE	.145	3.68	.232	5.89	16.3	60	50	1.8
											100	2.5
											200	3.4
											400	5.4
											700	6.9
1000	8.2											
355591802	18 (1 PR)	7/w BC	Unshielded	PP	.066	1.68	.460	11.68	22.5	60	50	1.8
											100	2.5
											200	3.4
											400	5.4
											700	6.9
1000	8.2											

Twisted Pair Colours: Black & Red

# CCTV CABLE

## RG-6

<b>Conductor</b>	Bare copper
<b>Jacket</b>	Overall PVC
<b>Max. Voltage</b>	300V
<b>Nominal Impedance</b>	75 ohms
<b>Approvals</b>	EU CMG FT4
<b>Applications</b>	CCTV plus audio, pan and tilt CCTV control



Product Code	AWG	Strand & Cond.	Shield/ Coverage	Insulation Material	Insulation Nominal OD		Nominal OD		Nom. Cap. (pF/ft)	Cable Weight (lbs/mft)	Nominal Attenuation	
					in	mm	In	mm			mHz	Db/100ft
35561802	18 (CX)	Solid BC	95% BCB	FPE	.180	4.57	.266	6.76	16.3	69	50	1.5
											100	2.1
											200	3.1
											400	4.5
											700	5.9
1000	7.3											
35561802	18 (1 PR)	7/w BC	Unshielded	PP	.066	1.68	.500	12.70	21.5	69	50	1.5
											100	2.1
											200	3.1
											400	4.5
											700	5.9
1000	7.3											

Twisted Pair Colours: Black & Red

# PRECISION VIDEO CABLE



Product Code	RGU #	Conductor		Insul.	Jacket & O.D.	# of Shields & Type	Nom. Imped. (ohms)	Nom. Vel. Of Prop.	Nom. Cap. pF/ft	Approval Rating	Cable Weight (lbs/mft)	Nominal Attenuation	
		Size	Strand Type									mHz	Db/100 FT
35P752 Blue	RG59/U	20	Solid BC	PE	PVC .305	95% DTCB	75	66%	20.5	CSA/ FT4	72	50	2.0
												100	2.9
												200	4.3
												400	6.4
												700	9.0