

# MULTI-CONDUCTOR STRANDED FOIL & COPPER BRAID SHIELD CSA/FT4/UL

**Conductor** Stranded tinned copper  
**Insulation** 600V Colour coded semi-rigid PVC  
**Jacket** Grey PVC  
**Temperature** -20°C to 105°C



**Shield** Overall 100% aluminum foil with stranded tinned copper drain wire and 85% tinned copper braid.  
**Approvals** CSA Certified CMG listed to CM harmonized standard C22.2 No.214 and UL 444  
 Certified to CSA standard C22.2 No. 210.2 – Type AWM  
 UL listed CL2 per standard UL13

**Applications** For use in PA systems, unbalanced intercom systems, interconnecting cables, remote control circuits, telephones and low voltage relay control cables.

| Product Code | AWG Size | # of Cond. | Stranding | Drain Wire Size | Insulation Thickness (inches) | Jacket Thickness (inches) | Nominal O.D. (inches) | Cable Weight (lbs/mft) | Colour Code |
|--------------|----------|------------|-----------|-----------------|-------------------------------|---------------------------|-----------------------|------------------------|-------------|
| 35EB2203     | 22       | 3          | 7/30      | 24              | 0.010                         | 0.020                     | 0.170                 | 32                     | 2           |
| 35EB2209     | 22       | 9          | 7/30      | 24              | 0.010                         | 0.023                     | 0.251                 | 62                     | 2           |

