

MULTI-PAIR INTERCOM 105C (UNSHIELDED) CSA/FT4/UL

- Conductor** Solid tinned cop
- Insulation** Colour coded semi-rigid PV
- Jacket** Grey PV
- Temperature** 20C to +10
- Approvals** CSA certified CMG or CM to harmonized standard C22.2 No. 214 and UL 444. Certified to CSA standard C22.2 No. 210.2 - Type AWM. UL listed CL2 per standard UL13
- Applications** Intercom systems, signal systems, annunciators, multiple speaker systems, control circuits, nurse's call systems

Product Code	Cond. Size	# of Pairs	Cond. Strand	Nom. In-sul. Thick. (Inchs)	Nom. Jacket Thick (Inchs)	Sgstd Wrkn Vltge	Nom. O.D. (Inchs)	Colour Code	Ship. Wght Lbs/Mft
35CA2201	22	1	solid	0.01	0.023	600	0.142	3	16
35CA2202	22	2	solid	0.01	0.023	600	0.2	3	24
35CA2203	22	1	solid	0.01	0.023	600	0.213	3	32
35CA2204	22	4	solid	0.01	0.023	600	0.233	3	40
35CA2206	22	6	solid	0.01	0.023	600	0.265	3	52

ele02_mpair_02