

# SVO RETRACTILE CABLE CORD

**Conductor** Standard bare copper  
**Insulation** PVC  
**Jacket** Black, oil resistant thermoset  
**Temperature** +90°C  
**Voltage** 300V  
**Applications** Designed as power supply cord on machine tools, communication equipment, test equipment, power and distribution equipment, home appliances, lighting, mobile controls and numerous other applications.  
**Approvals** CSA C22.2 No. 49, UL-62, RoHS Compliant  
**Colour Code** Black, White, Green



Product Code	Cond. Size	# of Cond.	Cond. Strand	Cable O.D. (Inches)	Coil O.D. (inches)	AMPS*	Ship. Weight lbs/mft
18CD1802	18	2	41x34	0.26	7/8	7	1.3
18CD1803	18	3	41x34	0.275	1	7	1.5

\*Ampacities (Amps per conductor) are based on 30°C ambient temperature in air, 90°C conductor temperature.

Product Code	Retracted Length	Extended Length	Tangent Lead Both Ends
18CA1802	12 Inches	5 Feet	12 Inches
18CB1802	24 Inches	10 Feet	6 Inches
18CC1802	36 Inches	15 Feet	6 Inches
18CD1802	48 inches	20 Feet	6 Inches
18CE1802	8 Feet	40 Feet	6 Inches

# SJO RETRACTILE CABLE CORD

**Conductor** Standard bare copper  
**Insulation** Rubber  
**Jacket** Black, oil resistant thermoset  
**Temperature** +90°C  
**Voltage** 300V



**Applications** Designed as power supply cord on machine tools, communication equipment, test equipment, power and distribution equipment, home appliances, lighting, mobile controls and numerous other applications.

**Approvals** CSA, UL

**Colour Code** 2c-Black, White 3c-Black, White, Green 4c-Black, White, Green, Red

Product Code	Cond. Size	# of Cond.	Cond. Strand	Cable O.D. (Inches)	Coil O.D. (inches)	AMPS*	Ship. Weight lbs/mft
18DD1802	18	2	41x34	0.32	1 3/16	7	1.8
18DD1803	18	3	41x34	0.35	1 3/8	7	2.3
18DD1804	18	4	41x35	0.385	1 7/16	7	2.5
18DD1602	16	2	65x34	0.385	1 3/8	10	2.3
18DD1603	16	3	65x34	0.39	1 7/16	10	2.9
18DD1604	16	4	65x34	0.425	1 1/2	8	3.6

\*Ampacities (Amps per conductor) are based on 30°C ambient temperature in air, 90°C conductor temperature.

Product Code	Retracted Length	Extended Length	Tangent Lead Both Ends
18DA1802	12 Inches	5 Feet	12 Inches
18DB1802	24 Inches	10 Feet	6 Inches
18DC1802	36 Inches	15 Feet	6 Inches
18DD1802	48 inches	20 Feet	6 Inches
18DE1802	8 Feet	40 Feet	6 Inches