

SO RETRACTILE CABLE CORD

Conductor Standard bare copper
Insulation Rubber
Jacket Black, oil resistant thermoset
Temperature +90°C
Voltage 600V
Applications Designed as power supply cord on machine tools, communication equipment, test equipment, power and distribution equipment, home appliances, lighting, mobile controls and numerous other applications.



Approvals CSA, UL
Colour Code Up to 6c-Black, White, Green, Red, Yellow, or Orange, Brown 18-10c and 16-8c-Black, White, Green, Red, Orange, Blue, Wht/Blk tracer, Red/Blk tracer, Grn/Blk tracer, Org/Blk tracer. 14-7c and 12-7c-Black, White, Green, Red, Orange, Blue, Wht/Blk tracer

Product Code	Cond. Size	# of Cond.	Cond. Strand	Cable O.D. (Inches)	Coil O.D. (inches)	AMPS*	Ship. Weight lbs/mft
18ED1803	18	3	41x34	.350	1 3/8	7	2.3
18ED1804	18	4	41x34	.385	1 7/16	7	2.5
18ED1810	18	10	41x35	.650	2 3/8	4.9	7.2
18ED1603	16	3	65x34	.470	1 13/16	10	3.9
18ED1604	16	4	65x34	.500	1 7/8	8	4.3
18ED1605	16	5	65x34	.540	2 1/8	8	5.5
18ED1606	16	6	65x34	.545	2	8	5.7
18ED1608	16	8	65x34	.626	2 1/2	7	7.4
18ED1402	14	2	41x30	.540	2 1/8	15	4.6
18ED1403	14	3	41x30	.560	2 1/8	15	5.7
18ED1404	14	4	41x30	.605	2 1/4	12	6.6
18ED1407	14	7	41x30	.720	2 7/8	7	11
18ED1203	12	3	65x30	.635	2 3/8	20	7.33
18ED1204	12	4	65x30	.678	2 3/8	16	8.7
18ED1207	12	7	65x30	.775	2 5/8	16	13
18ED1004	10	4	104x30	.745	2 3/4	20	13.2

*Ampacities (Amps per conductor) are based on 30°C ambient temperature in air, 90°C conductor temperature.

Product Code	Retracted Length	Extended Length	Tangent Lead Both Ends
18EA1803	12 Inches	5 Feet	12 Inches
18EB1803	24 Inches	10 Feet	6 Inches
18EC1803	36 Inches	15 Feet	6 Inches
18ED1803	48 inches	20 Feet	6 Inches
18EE1803	8 Feet	40 Feet	6 Inches