


# 4 CONDUCTOR ALUMINUM TECK 90 (XLPE) -40°C



Product Code	AWG Size	Bonding AWG (Bare Grnd)	Under Armour Diameter		Over Armour Diameter		Outer Jacket Diameter		Weight Aluminum	
			In	mm	In	mm	In	mm	lbs/mft	kg/km
<b>600 VOLTS</b>										
19N0604	6	8	0.811	20.60	1.078	27.40	1.220	31.00	540	890
19N0404	4	8	0.976	24.80	1.240	31.50	1.385	35.20	787	1171
19N0204	2	6	1.090	27.70	1.358	34.50	1.480	37.60	1032	1536
19N0104	1	6	1.232	31.30	1.499	38.10	1.618	41.10	1093	1626
19N04	1/0	6	1.303	33.10	1.598	40.60	1.775	45.10	1365	2032
19N004	2/0	6	1.389	35.30	1.670	42.40	1.846	46.90	1536	2286
19N0004	3/0	4	1.472	37.40	1.751	44.50	1.925	48.90	1694	2521
19N00004	4/0	4	1.669	42.40	2.019	51.30	2.200	55.90	2163	3219
19N2504	250	4	1.854	47.10	2.204	56.00	2.374	60.30	2511	3738
19N3504	300	3	2.086	53.00	2.437	61.90	2.606	66.20	3093	4603
19N5004	500	3	2.374	60.30	2.724	69.20	2.901	73.70	3956	5887
19N7504	750	2	2.925	74.30	3.275	83.20	3.453	87.70	5566	8283
<b>1000 VOLTS</b>										
19P0604	6	8	0.933	23.70	1.197	30.40	1.322	33.60	693	1032
19P0404	4	8	1.039	26.40	1.303	33.10	1.472	37.40	865	1287
19P0204	2	6	1.165	29.60	1.441	36.60	1.578	40.10	1027	1529
19P0104	1	6	1.338	34.00	1.606	40.80	1.787	45.40	1294	1927
19P04	1/0	6	1.425	36.20	1.720	43.70	1.902	48.30	1505	2241
19P004	2/0	6	1.519	38.60	1.811	46.00	1.984	50.40	1692	2519
19P0004	3/0	4	1.642	41.70	1.980	50.30	2.094	53.20	1959	2916
19P00004	4/0	4	1.811	46.00	2.161	54.90	2.342	59.50	2351	3499
19P2504	250	4	1.980	50.30	2.331	59.20	2.492	63.30	2671	3976
19P3504	350	3	2.216	56.30	2.567	65.20	2.728	69.30	3261	4853
19P5004	750	3	2.499	63.50	2.850	72.40	3.043	77.30	4181	6222
19P7504	1000	2	2.984	75.80	3.335	84.70	3.531	89.70	5767	8582