

1 CONDUCTOR 5KV SHIELDED TECK CONNECTORS

# Of Cond.	AMP 30°C Ambient	O-Z Gedney	T&B	Prysmian WTF*		Nexans WTF*	
				Iberville	T&B	Iberville	T&B
4/0	385	JMC100138	10469/ST100-469	TCA-125-151	10469/ST100-469	TCA-125-151	10469/ST100-469
250	425	JMC125163	10470/ST100-470	TCA-125-151	10470/ST100-470	TCA-125-151	10470/ST100-470
300	480	JMC125163	10470/ST100-470	TCA-125-151	10470/ST100-470	TCA-125-151	10470/ST100-470
350	530	JMC125163	10470/ST100-470	TCA-125-167	10470/ST100-470	TCA-125-167	10470/ST100-470
400	575	JMC125163	10470/ST100-470	TCA-125-167	10470/ST100-470	TCA-125-167	10470/ST100-470
500	660	JMC125188	10471/ST100-471	TCA-150-182	10471/ST100-471	TCA-150-182	10471/ST100-471
600	740	JMC125188	10471/ST125-471	TCA-150-192	10471/ST125-471	TCA-150-192	10471/ST125-471
750	845	JMC150220	10473/ST125-473	TCA-150-208	10473/ST125-473	TCA-150-208	10473/ST125-473
1000	1000	JMC150220	10473/ST125-473	TCA-200-231	10473/ST125-473	TCA-200-231	10473/ST125-473

*Water Tight Fittings

Other connector types available: Dry, Copper Free Aluminum, Slim Design, Angled
Ensure that only non-magnetic connectors are used.