


2 CONDUCTOR TECK 90 (XLPE) -40°C 1000V



Product Code	AWG Size	Bonding AWG (bare copper)	Insulation Thickness		Inner Jacket Thickness		Appropriate Diameters				Weight Aluminum (Armoured)			
			Inches	mm	Inches	mm	Inner Jacket		Armour		Outer Covering		lbs/mft	kg/km
19C1202	12	14	.045	1.14	.045	1.14	0.464	11.78	0.696	17.67	0.794	20.17	272	405
19C1002	10	12	.045	1.14	.045	1.14	0.510	12.95	0.750	19.05	0.848	21.54	296	440
19C0802	8	10	.045	1.14	.060	1.52	0.590	14.98	0.819	20.80	0.926	23.52	407	606
19C0602	6	8	.060	1.52	.060	1.52	0.718	18.25	0.945	24.00	1.055	26.80	545	811
19C0402	4	8	.060	1.52	.060	1.52	0.812	20.61	1.084	27.53	1.188	30.18	742	1104
19C0202	2	6	.060	1.52	.080	2.03	0.963	24.45	1.235	31.37	1.339	34.01	1029	1531
19C0102	1	6	.080	2.03	.080	2.03	1.110	28.20	1.385	35.18	1.514	38.45	1252	1863
19C02	1/0	6	.080	2.03	.080	2.03	1.185	30.09	1.454	36.93	1.558	39.57	1451	2159
19C002	2/0	6	.080	2.03	.080	2.03	1.263	32.09	1.533	38.94	1.641	41.68	1675	2493
19C0002	3/0	4	.080	2.03	.080	2.03	1.358	34.50	1.633	41.48	1.762	44.75	2031	3022
19C00002	4/0	4	.080	2.03	.080	2.03	1.463	37.16	1.731	43.97	1.863	47.32	2385	3549