


14 AWG MULTI-CONDUCTOR TECK 90 (XLPE) -40°C 600V



Product Code	No. of Cond.	Bonding AWG (Bare Copper)	Insulation Thickness		Inner Jacket Thickness		Inner Jacket Diameter		Armour Diameter		Outer Jacket Diameter		Weight Aluminum (Armoured)	
			Inches	mm	Inches	mm	Inches	mm	Inches	mm	Inches	mm	lbs/mft	kg/km
19A1402	2	14	.030	0.76	0.045	1.14	0.369	9.37	0.600	15.24	0.688	17.48	191	284
19A1403	3	14	.030	0.76	0.045	1.14	0.390	9.91	0.621	15.77	0.709	18.01	225	335
19A1404	4	14	.030	0.76	0.045	1.14	0.444	11.27	0.676	17.17	0.761	19.33	266	396
19A1405	5	14	.030	0.76	0.045	1.14	0.472	11.99	0.703	17.86	0.787	19.99	306	455
19A1406	6	14	.030	0.76	0.045	1.14	0.515	13.08	0.743	18.87	0.828	21.03	316	471
19A1407	7	14	.030	0.76	0.045	1.14	0.522	13.26	0.755	19.18	0.844	21.44	338	502
19A1408	8	14	.030	0.76	0.060	1.52	0.597	15.16	0.825	20.96	0.909	23.09	384	571
19A1410	10	14	.030	0.76	0.060	1.52	0.671	17.04	0.898	22.81	0.984	24.99	448	667
19A1412	12	14	.030	0.76	0.060	1.52	0.700	17.78	0.927	23.55	1.013	25.73	489	728
19A1415	15	14	.030	0.76	0.060	1.52	0.750	19.05	0.990	25.15	1.090	27.69	583	868
19A1420	20	14	.030	0.76	0.060	1.52	0.850	21.59	1.105	28.07	1.189	30.20	766	1140
19A1425	25	14	.030	0.76	0.080	2.03	0.983	24.99	1.239	31.47	1.326	33.68	852	1268
19A1430	30	14	.030	0.76	0.080	2.03	1.060	26.92	1.311	33.30	1.399	35.53	995	1481
19A1440	40	14	.030	0.76	0.080	2.03	1.179	29.95	1.431	36.35	1.519	38.86	124	1822
19A1450	50	14	.030	0.76	0.080	2.03	1.282	32.56	1.535	38.99	1.642	41.71	1468	2184

ewc02_std_600v_01