


16 AWG ARMCON



Product Code	# of Cond.	Amp @ 30°C	Nominal OD inner jacket		Nominal OD Armour		Nominal OD Outer Jacket		Weight Aluminum (Armoured)	
			mm	In	mm	In	mm	In	lbs/mft	kg/km
46A1602-40	2	10	8.7	0.34	14.5	0.57	17.5	0.698	295	440
46A1603-40	3	10	9.2	0.36	15.2	0.6	18.1	0.71	325	485
46A1604-40	4	8	10	0.39	15.8	0.62	18.8	0.74	357	532
46A1605-40	5	8	10.9	0.43	16.4	0.65	19.4	0.76	389	580
46A1606-40	6	8	11.8	0.46	17.7	0.7	20.7	0.81	431	643
46A1607-40	7	7	12.7	0.5	18.3	0.72	21.3	0.84	464	692
46A1608-40	8	7	14.4	0.57	20.2	0.8	23.2	0.91	541	807
46A1610-40	10	7	15.6	0.62	21.5	0.85	24.5	0.96	604	901
46A1612-40	12	7	16.1	0.64	21.5	0.85	24.5	0.96	645	962
46A1615-40	15	7	17.8	0.7	23.4	0.92	26.4	1.04	740	1104
46A1620-40	20	7	19.7	0.78	26.4	1.04	29.6	1.17	968	1444
46A1625-40	25	6	22.9	0.9	29.6	1.17	32.8	1.29	1186	1769
46A1630-40	30	6	24.1	0.95	30.9	1.22	34.1	1.34	1313	1958
46A1640-40	40	6	27.9	1.1	34.7	1.37	38.2	1.5	1623	2420
42A1650-40	50	6	31.3	1.23	37.8	1.49	41.3	1.63	1897	2829
42A1660-40	60	6	32.3	1.27	38.6	1.52	42	1.65	2159	3220

ewc03_armcon_01