


CORFLEX 600V INSULATED WIRE ALUMINUM



Product Code	Size	Approximate Diameter				Approx Net Cable Weight				Connectors		Minimum# Bending Radius		Ampacity 30°C Ambient (amps)
		Over Sheath		Over PVC Jacket		Without Jacket		With PVC Jacket		Type D (Dry)	Type W (Wet)	mm	in	
		mm	in	mm	in	kg/km	lbs/mft	kg/km	lbs/mft					
2CA01	1/0	19.1	.75	21.8	.86	331	223	454	305	20D3	20W3	203	8	190
2CA001	2/0	19.6	.77	22.4	.88	380	255	506	340	20D3	20W3	203	8	220
2CA0001	3/0	20.3	.80	23.1	.91	435	292	566	380	20D3	20W3	229	9	255
2CA00001	4/0	20.8	.82	23.4	.92	497	334	640	430	20D3	20W3	229	9	300
2CA2501	250	24.1	.95	26.9	1.06	604	406	759	510	25D3	25W3	254	10	330
2CA3001	300	25.1	.99	27.7	1.09	687	462	848	570	25D3	25W3	254	10	375
2CA3501	350	25.3	1.00	27.9	1.10	756	508	930	625	25D3	25W3	254	10	415
2CA4001	400	29.7	1.17	32.3	1.27	928	624	1116	750	30D4	30W4	305	12	450
2CA5001	500	30.3	1.19	33.0	1.30	1074	722	1281	861	30D4	30W4	305	12	515
2CA6001	600	35.1	1.38	37.6	1.48	1326	891	1548	1040	35D5	35W5	356	14	585
2CA7501	750	35.7	1.40	38.3	1.51	1561	1044	1802	1211	35D5	35W5	402	15.8	670
2CA10001	1000	40.3	1.59	43.5	1.71	2025	1361	2358	1584	40D5	40W5	457	18	800

ewc05_al_armour_03