

# TINNED COPPER WIRE

(SOFT, MEDIUM OR HARD DRAWN)

**Description** Bare copper conductors available in various tempers and sizes. Coated copper conductors, stranded, available in various sizes but in soft temper only.

**Application** Used in overhead electrical transmission and distribution, for grounding electrical systems where high conductivity and flexibility is required. Suitable for numerous other applications.

**Specification** ASTM B-1 Hard-Drawn Copper Wire  
 ASTM B-2 Medium-Hard-Drawn Copper Wire  
 ASTM B-3 Soft or Annealed Copper Wire  
 ASTM B-8 Concentric-Lay-Stranded Copper Conductors, Hard, Medium-Hard, or Soft  
 ASTM B-33 Tinned Soft Or Annealed Copper Wire



## Stranded

Product Code	Size	Stranding	Nominal OD		Weight	
			Inch	mm	lbs/mft	kgs/km
2BT0607	6	7/.0612	0.184	4.67	81	119
2BT0207	2	7/.0974	0.292	7.42	205	305
2BT0019	2/0	19/.0837	0.418	10.62	411	612
2BT000019	4/0	19/.1055	0.528	13.41	653	952
2BT25037	250	37/.0822	0.575	14.61	772	1149
2BT50037	500	37/.1162	0.1162	2.96	1543	2296