

SEW-2 200°C 600V BRAIDED SILICONE RUBBER

Ratings/ Approvals UL Style 3071, 3074, 3075, 3231 SF-2, CSA SEW-2, 200°C/600V



Construction Stranded tin or nickel plated copper conductor
Extruded Silicone Rubber
Treated Braided Fiberglass

Jacket* Standard color coding - available in color or stripes

Product Code	AWG (Stranding)	OD	Weight/mft	UL	CSA
-	24(7)	.099"	6	3231	AWM I A/B
-	22(7)	.104"	7	3231	SEWF-2/AWM I A/B
-	20(7)	.111"	8	3231	SEWF-2/AWM I A/B
404000	18(7)	.121"	11	3231/3071/SF-2	SEW-2/AWM I A/B
404100	16(7)	.133"	15	3231/3071/SF-2	SEW-2/AWM I A/B
404200	14(7)	.146"	21	3231/3071/SF-2	SEW-2/AWM I A/B
404300	12(19)	.163"	30	3231/3074/SF-2	SEW-2/AWM I A/B
404400	10(19)	.218"	50	3231/3075/SF-2	SEW-2/AWM I A/B
404500	8(19)	.286"	82	3231	SEW-2/AWM I A/B
404600	6(19)	.326"	119	3231	SEW-2/AWM I A/B
404700	4(133)	.406"	182	3231	SEW-2/AWM I A/B
404800	2(259)	.474"	275	3231	SEW-2/AWM I A/B
404900	1(259)	.557"	353	3231	SEW-2/AWM I A/B
405000	1/0(259)	.595"	436	3231	SEW-2/AWM I A/B
405010	2/0(259)	.685"	535	3231	SEW-2/AWM I A/B
405020	3/0(259)	.735"	669	3231	SEW-2/AWM I A/B
405030	4/0(259)	.806"	804	3231	SEW-2/AWM I A/B

*Many colours available, please inquire