

Coaxial Cable

(CATV/VIDEO/COMPUTER/TRANSMISSION)

Conductor Copper Clad Steel (CCS), Solid Bare Copper (BC) or Stranded Tinned Copper (STC) as indicated.



Insulation Foamed PE (FPE), Gas Injected PE (GPE), Cellular PE (CPE), and PE

Jacket PE or PVC as Indicated

Shield Aluminum Braid (AB), Bare Copper Braid (BCB), Copper Clad Aluminum (CCA), Tinned Copper Braid (TCB), Double Bare Copper Braid (DTCB) as indicated

Approvals CSA, FT1, FT4, FT6 as indicated

Applications CATV - For distributing television signals
CCTV - for surveillance, connecting security cameras, DVR or monitor

Product Code Jacket Colour	RGU #	Conductor		Insul.	Jacket & O.D.	Shield	Nom. Imped. (ohms)	Nom. Velocity of Prop.	Nom. Cap. pF/ft	Approval	Cable Weight (lbs/mft)	50Nominal Attenuation	
		AWG Size	Strand Type									mHz	Db/100 FT
35L61-61 Black	6/U Burial	18	CCS	FPE	PE .272	Foil & 60% AB Flooded	75	82%	16.2	CSA/FT6	23	50	1.41
												100	1.92
												200	2.64
												400	3.93
												700	5.05
												900	5.79
35L66U- Black	6/U Burial	18	Solid BC	GPE	PE .274	95% BCB Flooded	75	81%	17.4	CSA/FT6	37	50	1.5
												100	2.1
												200	3.1
												400	4.4
												700	5.9
												1000	7.3
35M65U Black	6/U	18	Solid BC	FPE	PVC .266	95% BCB	75	83%	16.3	CSA/FT4	36	50	1.5
												100	2.0
												200	2.9
												400	4.2
												700	5.6
												900	6.4
35M112 Black	11/U	14	Solid CCS	FPE	PVC .395	60% AB	75	82%	16.2	CSA/FT4	80	50	0.89
												100	1.21
												200	1.68
												400	2.37
												700	3.27
												900	3.77
35L594 Black	59/U Burial	20	Solid BC	CPE	PVC .242	95% CCA Water Blocking Tape	75	78%	17.3		23	50	1.8
												100	2.7
												200	3.8
												500	6.3
												900	8.5

Continued On Next Page

COAX_CVC.pdf

Coaxial Cable

(CATV/VIDEO/COMPUTER/TRANSMISSION)

Continued from Previous Page

Product Code Jacket Colour	RGU #	Conductor		Insul.	Jacket & O.D.	Shield	Nom. Imped. (ohms)	Nom. Velocity of Prop.	Nom. Cap. pF/ft	Approval	Cable Weight (lbs/mft)	50Nominal Attenuation	
		AWG Size	Strand Type									mHz	Db/100 FT
35M593U Black White	59/U	22	Solid CCS	PE	PVC 0.240	95% BCB	75	78%	17.3	CSA/FT4	36	50	2.0
												100	3.0
												200	4.4
												500	6.9
												900	9.2
35M594U Black White	RG 59/U	20	Solid BC	FPE	PVC 0.242	95% BCB	75	82%	16.2	CSA/FT4	36	50	2.1
												100	2.9
												200	4.1
												500	6.6
												900	8.8
35M582U Black	58/U	20	Solid BC	PE	PVC 0.195	95% TCB	53.5	66%	28.5	CSA/FT4	32	50	3.1
												100	4.5
												200	6.8
												400	10.0
												700	14.0
35L2142 Black	214/U	13	7 x 21 STC	PE	PVC 0.425	98% DTCTB	50	66%	29.5	CSA/FT1	134	900	16.0
												50	1.6
												100	2.3
												200	3.1
												400	5.0
35L2143 Black	213/U	13	7 x 0.296 STC	PE	PVC 0.425	95% DTCTB	50	66%	30.8	CSA/FT4	134	700	6.9
												900	8.0
												1000	9.0
												100	2.3
												200	3.1
35L2131 Black	213/U	13	7 x 21 BC	PE	PVC 0.405	95% BCB	50	66%	30.8	CSA/FT1	100	400	5.0
												900	8.0
												50	1.35
												100	2.1
												200	3.0
35L1741 Black	174/U	26	7 x 34 BC	PE	PVC 0.100	95% TCB	50	66%	30.8	CSA/FT1	10	400	4.8
												1000	8.2
												50	6.5
												100	8.8
												200	13.0
												400	20.0

COAX_CVC.pdf

