

DIRECT BURIAL MULTI-CONDUCTOR UNSHIELDED

Conductor Stranded tinned copper
Insulation Colour coded semi-rigid PVC
Jacket Black high density Polyethylene
Temperature -20°C to 80°C



Applications For direct earth burial low voltage applications on PA, signal, annunciator, speaker and sound systems.

Product Code	AWG Size	# of Cond.	Stranding	Insulation Thickness (inches)	Jacket Thickness (inches)	Nominal O.D. (inches)	Cable Weight (lbs/mft)	Colour Code
35AE1802	18	2	16/30	0.012	0.025	0.200	19	7
35AE1804	18	4	16/30	0.012	0.025	0.231	34	1
35AE1602	16	2	26/30	0.015	0.025	0.239	28	7
35AE1604	16	4	26/30	0.015	0.025	0.277	50	1

Non-CSA

Chart No. 1 Multi-Conductor

Cond. #	Colour
1	Black
2	White
3	Red
4	Green
5	Brown
6	Blue
7	Orange
8	Yellow
9	Purple
10	Grey
11	Pink
12	Tan

Chart No. 7 Multi-Conductor

Cond. #	Colour
1	Black
2	Red
3	White
4	Green
5	Orange
6	Blue
7	Brown
8	Yellow
9	Purple
10	Grey
11	Pink
12	Tan

DB_MC_U.pdf