

# SJO Retractable Cable Cord

- Conductor** Stranded bare copper
- Insulation** Thermoset rubber
- Jacket** Black, oil resistant thermoset
- Temperature** +90°C
- Voltage** 300V
- Applications** Designed as power supply cord on machine tools, communication equipment, test equipment, power and distribution equipment, home appliances, lighting, mobile controls and numerous other applications.
- Approvals** CSA, UL
- Colour Code** 2C Black, white  
3C Black, white, green  
4C Black, white, green, red



Product Code	AWG Size	# of Cond.	Cond. Strand	Cable O.D. (Inches)	Coil O.D. (inches)	Retracted Length (Inches)	Extended Length (Feet)	Tangent Lead Both Ends (Inches)	AMPS*	Ship. Weight lbs/mft
18DD1802	18	2	41x34	0.32	1.14	48	20	6	10	1.6
18DD1803	18	3	41x34	0.35	1.21	48	20	6	10	2.2
18DD1804	18	4	41x34	0.38	1.385	48	20	6	7	3.2
18DD1602	16	2	65x34	0.36	1.345	48	20	6	13	2.2
18DD1603	16	3	65x34	0.385	1.4	48	20	6	13	3.0
18DD1604	16	4	65x34	0.42	1.465	48	20	6	10	4

\*Ampacities (Amps per conductor) are based on 30°C ambient temperature in air, 90°C conductor temperature.  
Also available in 36", 24" & 12" retracted lengths with 1:5 ratio extended lengths - please inquire for further details

SJO\_RCC.pdf