

Type PPC/SC Stage & Lighting Entertainment Cable

- Conductor** Flexible stranded bare annealed copper
- Jacket** Black oil and weather resistant CSPE thermoset
- Temperature** -50°C to +105°C (UL 105°C)
- Voltage** 600V
- Applications** Designed for portable power and lighting applications in the entertainment industry including motion picture, television, theatres, stage and similar locations. Suitable for both indoor and outdoor uses.
- Approvals** CSA FT5 Type PPC C22.2 No. 96, UL Type SC Subject 1680, IEEE 383, VW-1, MSHA
- Packaging** Long length Reels cut to length



Product Code	AWG Size	# of Cond.	Cond. Strand	Nom. O. D. (Inches)	Current AMPS	Ship. Weight lbs/mft
16FA0801	8	1	168x30	0.385	80	110
16FA0601	6	1	258x30	0.371	105	128
16FA0401	4	1	412x30	0.429	140	186
16FA0201	2	1	649x30	0.509	190	279
16FA0101	1	1	817x30	0.613	220	378
16FA01	1/0	1	1033x30	0.672	260	452
16FA001	2/0	1	1289x30	0.697	300	537
16FA0001	3/0	1	1650x30	0.773	350	666
16FA00001	4/0	1	2062x30	0.814	405	807

*Ampacities (Amps per conductor) are based on 30°C ambient temperature in air, 90°C conductor temperature.